

# TECHNICAL DATASHEET

## OM - 1140

<b>Print Speed</b>	400 cps (Fastest Draft); 300 cps (Draft), 75 cps (NLQ) at 10 cpi
<b>Resolution</b>	Up to 144 x 240 dpi
<b>Throughput</b>	290 pages per hour
<b>Character Density</b>	10, 12, 15, 17.1, 20 cpi
<b>Line Density</b>	1, 2, 3, 4, 6, 8 lpi
<b>Printhead Life</b>	400 million strokes per wire
<b>Memory</b>	
<b>Connectivity</b>	<b>Standard</b> USB 2.0 <b>Optional</b> Parallel IEEE 1284, Serial RS-232C, Ethernet (10/100)
<b>Device Management</b>	Config-Tool via USB
<b>Emulations Standard</b>	IBM ProPrinter 2380plus, Epson ESC P/2
<b>Fonts</b>	Draft, Quadrato, Courier, HS Draft, OCR-A/B, EAN-8, EAN-13, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, POSTNET
<b>Consumables</b>	Ribbon: 9 million characters
<b>Paper Handling</b>	<b>Standard</b> Push tractor and friction <b>Optional</b> Roll holder
<b>Number of Copies</b>	1 original + 4 copies
<b>Paper Types</b>	Cut sheets, continuous forms, multi-part forms
<b>Paper Sizes</b>	Width: 95 to 267 mm Length: 114 to 362 mm (Cut sheet); 114 to 558 mm (Fanfold)
<b>Paper Weight</b>	52 - 100 g/m <sup>2</sup>
<b>Dimensions (W x D x H)</b>	369 x 283 x 130 mm
<b>Physical Weight</b>	5 kg
<b>Acoustics</b>	57 dB(A)
<b>Power Voltage</b>	100- 230 V - 50/60 Hz
<b>Power Consumption</b>	Less then 1,2 Watt Sleep-Mode
<b>Temperature</b>	+5° to +35° C; 10% to 80% humidity
<b>Workload</b>	6,000 pages per month
<b>MTBF</b>	12,000 hours
<b>Driver</b>	Windows XP/Vista/7/8.1 and Server 2003/2008/2012