

TECHNICAL DATASHEET

OM - 1145

Print Speed	450 cps (Fastest Draft); 300 cps (Draft), 100 cps (LQ) at 10 cpi
Resolution	Up to 360 x 360 dpi
Throughput	296 pages per hour
Character Density	10, 12, 15, 16.6, 17.1, 20, 24 cpi
Line Density	1, 2, 3, 4, 6, 8 lpi
Printhead Life	400 million strokes per wire
Memory	Up to 256 kb
Connectivity	Standard USB 2.0 Optional Parallel IEEE 1284, Serial RS-232C, Ethernet (10/100)
Device Management	Config-Tool via USB
Emulations Standard	IBM ProPrinter 2390plus, Epson ESC P/2
Fonts	Draft, Roman, Sans Serif, Courier, Prestige, Script, Orator, Gothic, Souvenir, OCR -A/B, EAN-8, EAN-13, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, POSTNET
Consumables	Ribbon: 9 million characters
Paper Handling	Standard Push tractor and friction Optional Roll holder
Number of Copies	1 original + 6 copies
Paper Types	Cut sheets, continuous forms, multi-part forms
Paper Sizes	Width: 95 to 267 mm Length: 114 to 362 mm (Cut sheet); 114 to 558 mm (Fanfold)
Paper Weight	52 - 100 g/m ²
Dimensions (W x D x H)	369 x 283 x 130 mm
Physical Weight	5 kg
Acoustics	57 dB(A)
Power Voltage	100- 230 V - 50/60 Hz
Power Consumption	Less than 1,4 Watt Sleep-Mode
Temperature	+5° to +35° C; 10% to 80% humidity
Workload	6,000 pages per month
MTBF	12,000 hours
Driver	Windows XP/Vista/7/8.1 and Server 2003/2008/2012