

# TECHNICAL DATASHEET

## OM - 2610+

<b>Print Speed</b>	683 cps (Fastest Draft); 600 cps (HS - Draft), 513 cps (Draft), 114 cps (LQ) at 10 cpi
<b>Resolution</b>	Up to 360 x 360 dpi
<b>Throughput</b>	457 pages per hour (ECMA 132)
<b>Character Density</b>	10, 12, 15, 17.1, 20 cpi
<b>Line Density</b>	2, 3, 4, 6, 8, 12 lpi
<b>Printhead Life</b>	500 million impact per wire
<b>Memory</b>	
<b>Connectivity</b>	<b>Standard</b> Parallel (Bi-directional), USB 2.0 and Ethernet (10/100BaseT, IPv6) USB Host <b>Optional</b>
<b>Device Management</b>	WebPanel via Ethernet; Config-Tool via USB/Parallel
<b>Emulations Standard</b>	IBM ProPrinter XL24, Epson ESC P/2, MTPL + Barcode + LCP Epson FX 9-Nadel Emulation
<b>Fonts</b>	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 14 Barcodes and large character printing
<b>Consumables</b>	Ribbon: 15 million characters
<b>Paper Handling</b>	<b>Standard</b> One tractor useable as push (front or rear) or pull (top) version, continuous paper with straight paper path and park position, cut sheet front insertion, tear or front off <b>Optional</b> Additional push tractor (rear)
<b>Number of Copies</b>	1 original + 5 copies
<b>Paper Types</b>	Cut sheets, continuous forms, multi-part forms
<b>Paper Sizes</b>	Width: 76 to 420 mm; Length: 76 to 599 mm
<b>Paper Weight</b>	60 - 120 g/m <sup>2</sup>
<b>Dimensions (W x D x H)</b>	600 x 265 x 200 mm
<b>Physical Weight</b>	10.6 kg
<b>Acoustics</b>	<53 dB(A)
<b>Power Voltage</b>	100 - 240 V - autosensing
<b>Power Consumption</b>	60 Watt printing; <3 W Sleep Mode
<b>Temperature</b>	+10° to +40° C; 10% to 85% rel. humidity
<b>Workload</b>	20,000 pages per month
<b>MTBF</b>	20,000 hours
<b>Driver</b>	Windows 7/8/10 and Server 2008/2012 (32/64 Bit); SAP